

# FLESSIBILI DN 10 ACCIAIO INOX

FLESSIBILI PER SANITARI


# STAINLESS STEEL DN 10 FLEXIBLES

FLEXIBLES FOR SANITARIES

## APPLICAZIONI - APPLICATIONS



## MATERIALI - MATERIALS



- RACCORDI - FITTINGS:**  
A) Ottone CW614N e CW617N nichelato  
Brass CW614N and CW617N nickel plated

- BUSSOLE - SLEEVES:**  
B) Acciaio INOX AISI 304  
Stainless steel AISI 304

- TUBO - HOSE:**  
C) Treccia 7-8 fili in acciaio INOX AISI 304  
7-8 Wires Braid in steel INOX AISI 304  
D) Tubo interno: gomma EPDM atossico  
Internal pipe EPDM rubber, atoxic

## CARATTERISTICHE - FEATURES



**TEMPERATURA INSTALLAZIONE - INSTALLATION TEMPERATURE:**

Da -5°C a +90°C - From -5°C to +90°C



**PRESSIONE D'ESERCIZIO - WORKING PRESSURE:**

10 BAR



**PORTATA A 3 BAR - FLOW RATE AT 3 BAR:**

42 lit/min



**TEMPERATURA D'IMPIEGO - WORKING TEMPERATURE:**

-5°C - +90°C



**FORO MINIMO PASSAGGIO D'ACQUA - FITTING INNER DIAMETER:**

7 mm



**RAGGIO CURVATURA MINIMO - MINIMUM BENDING RADIUS:**

30 mm



**Ø INTERNO - INNER Ø:**

Ø 10 mm



**Ø ESTERNO - OUTER Ø:**

Ø 14 mm