

FLESSIBILI DN 8 ACCIAIO INOX

FLESSIBILI PER RUBINETTERIA E SANITARI


STAINLESS STEEL DN 8 FLEXIBLES

FLEXIBLES FOR FAUCETS AND SANITARIES

APPLICAZIONI - APPLICATIONS



MATERIALI - MATERIALS



RACCORDI - FITTINGS:

- A) Ottone CW614N e CW617N nichelato
Brass CW614N and CW617N nickel plated

BUSSOLE - SLEEVES:

- B) Acciaio INOX AISI 304
Stainless steel AISI 304

TUBO - HOSE:

- C) Treccia 7 fili in acciaio INOX AISI 304
7 Wires Braid in steel INOX AISI 304
D) Tubo interno: gomma EPDM atossico
Internal pipe EPDM rubber, atoxic

CARATTERISTICHE - FEATURES



TEMPERATURA INSTALLAZIONE - INSTALLATION TEMPERATURE:

Da -5°C a +90°C - From -5°C to +90°C



PRESSIONE D'ESERCIZIO - WORKING PRESSURE:

10 BAR



PORTATA A 3 BAR - FLOW RATE AT 3 BAR:

29 lit/min



TEMPERATURA D'IMPIEGO - WORKING TEMPERATURE:

-5°C - +90°C



FORO MINIMO PASSAGGIO D'ACQUA - FITTING INNER DIAMETER:

6 mm



RAGGIO CURVATURA MINIMO - MINIMUM BENDING RADIUS:

30 mm



Ø INTERNO - INNER Ø:

Ø 8 mm



Ø ESTERNO - OUTER Ø:

Ø 12 mm